



Special lubricants in the BECHEM Lubricator 125

Precise dosing

A lubricant dispenser for a wide range of applications

BECHEM special lubricants are designed for heavy-duty machine elements in numerous industries, including food, feed, pharmaceuticals, mining, paper, cement, steel, and port facilities. They are used where the highest demands are placed on lubricants, such as in dairies, coffee roasting plants, large slaughterhouses, canning and frozen

food factories, commercial kitchens, and the beverage industry.

Thanks to the BECHEM Lubricator 125, our special lubricants can also easily reach hard-to-access individual lubrication points.



The housing is weatherproof, corrosion-resistant, and offers protection against water ingress when submerged for an indefinite period of time (IP68)



The lubricant dispenser is adjustable for operating times from 1 to 12 months



Ready for use in any position. Even when upside down, the lubricator ensures precise lubrication



The lubricator is filled with 125 cm³ of lubricant, which can be dispensed at a maximum rate of 4.23 cm³ per day

Berulub FB 34-2

Berulub FB 34-2 is a high performance universal lubricant for the supply of grease lubricated, heavily loaded machine elements in plants in the pharmaceutical, cosmetics, food, and animal feed industries. The odorless and tasteless lubricating grease is free of MOAH, has good pumpability, offers excellent corrosion and wear protection, and has very good hot water and steam resistance. The lubricant is suitable for roller and plain bearings as well as for cam discs. Berulub FB 34-2 is H1-registered and Halal and Kosher certified.

load-bearing capacity and reliable corrosion protection. The lubricant is used in the roller bearings of pellet presses, in fan bearings, and in bearings that are exposed to higher temperatures. Berulub FG-H 2 EP is H1-registered, halal, and kosher certified.

Berusynth CB 180 H1

Berusynth CB 180 H1 is a synthetic high-temperature chain oil for the food, feed, and pharmaceutical industries. It performs well in conveyor chains of baking ovens and drying ovens. The oil offers excellent creep and wetting properties, is water-resistant and is suitable for high and low temperatures and loads. In addition, it ensures economical lubrication, reduces friction and provides excellent wear protection. Berusynth CB 180 H1 is allergen-free and certified halal and kosher.

Berulub FG-H 2 EP

Berulub FG-H 2 EP is a synthetic high-performance lubricating grease for the food and paper industry, pellet presses and railway technology, and is used to lubricate heavily loaded machine elements that are lubricated with grease. Berulub FG-H 2 EP is characterized by its high

Berutox FE 18 EP

Berutox FE 18 EP high-performance lubricating grease is ideal for lubricating high-speed roller bearings and electric motor bearings. It offers very good pumping properties, high-speed stability, and impressive EP properties. The grease has a wide operating temperature range, outstanding wear and corrosion protection, and very good water resistance. This ensures that functionality is maintained over the long term, even under demanding operating conditions.

BECHEM High-Lub LT 2 EP-SEB

Specially developed for the lubrication of roller and plain bearings, as well as for machines and equipment in the steel industry, this multi-purpose EP grease of NLGI class 2 impresses with its very wide operating temperature range. Even when absorbing water, BECHEM High-Lub LT 2 EP-SEB remains particularly corrosion-resistant and stable to kneading.

Berutox M 21 KN

Berutox M 21 KN is a long-term lubricating grease for extreme temperature conditions and is used particularly in the steel, textile, and paper industries. It offers very good consistency temperature behavior and high pumping ability, ensuring reliable lubrication even under changing operating conditions. Thanks to its pronounced EP properties, it effectively protects against wear and corrosion, thus extending the service life of machine components.

Berutox FH 28 KN

Berutox FH 28 KN long-term lubricating grease is ideal for diverse applications subject to extreme temperatures in the automotive, steel, and paper industries. It is characterized by excellent consistency-temperature behavior and very good corrosion and wear protection. The long-term lubricating grease is Halal and Kosher certified.



The lubricator is particularly suitable for supplying lubricant to individual lubrication points that are difficult to access. It is used at lubrication points on roller and plain bearings, linear guides, rollers, cam discs, shafts, spindles, seals, roller chains, and toothed chains. The BECHEM Lubricator 125 ensures perfect lubrication for up to a year and impresses with its cost-effectiveness, time savings, occupational safety, and hygiene.

Dosage to the point

BECHEM Lubricator 125



Information on the compliance with regulations and religious dietary rules to be taken from our sales documentation

LUBRICATION SOLUTIONS FOR INDUSTRY

CARL BECHEM GMBH · Weststr. 120 · 58089 Hagen · Germany · Phone +49 2331 935-0 · bechem@bechem.de · www.bechem.com